

1 **CLAIMS**

2 1. A method of factoring operating system functions comprising:  
3 defining criteria that governs how functions of an operating system are to  
4 be factored into one or more groups;  
5 factoring the functions into one or more groups based upon the criteria; and  
6 associating groups of functions with programming objects that have data  
7 and methods, wherein the methods correspond to the operating system functions.

8  
9 2. The method of claim 1, wherein the programming objects have  
10 interfaces through which the methods can be accessed.

11  
12 3. The method of claim 1, wherein the programming objects comprise  
13 COM objects.

14  
15 4. The method of claim 1, wherein said factoring comprises creating a  
16 hierarchy of object interfaces in which certain interfaces can inherit from other  
17 interfaces.

18  
19 5. The method of claim 1, wherein said factoring comprises creating a  
20 hierarchy of object interfaces in which certain interfaces can aggregate with other  
21 interfaces.

22  
23 6. The method of claim 1 further comprising instantiating a plurality of  
24 programming objects across a process boundary.  
25

1           7.    The method of claim 1, further comprising instantiating a plurality of  
2 programming objects across a machine boundary.

3  
4           8.    The method of claim 1, wherein the criteria is based, at least in part,  
5 on the manner in which particular functions behave.

6  
7           9.    The method of claim 8, wherein the manner includes a consideration  
8 of the types of operating system resources that are associated with the operation of  
9 a function.

10  
11          10.   The method of claim 8, wherein the manner includes a consideration  
12 of whether a particular function creates an operating system resource.

13  
14          11.   The method of claim 8, wherein the manner includes a consideration  
15 of whether a particular function operates upon an operating system resource.

16  
17          12.   The method of claim 1, wherein the criteria is based, at least in part,  
18 on the manner in which particular functions behave, wherein the manner includes:

19           a consideration of the types of operating system resources that are  
20 associated with the operation of a function; and

21           a consideration of whether a particular function creates an operating system  
22 resource.

1       **13.**     The method of claim 1, wherein the criteria is based, at least in part,  
2     on the manner in which particular functions behave, wherein the manner includes:  
3       a consideration of the types of operating system resources that are  
4     associated with the operation of a function call; and  
5       a consideration of whether a particular function operates upon a given  
6     operating system resource.

7  
8       **14.**     A method of factoring operating system functions comprising:  
9     factoring a plurality of operating system functions that are used in  
10    connection with operating system resources into first groups based upon first  
11    criteria;  
12       factoring the first groups into individual sub-groups based upon second  
13    criteria; and  
14       assigning each sub-group to its own programming object interface, wherein  
15    a programming object interface represents a particular object's implementation of  
16    its collective methods.

17  
18       **15.**     The method of claim 14, wherein the first criteria is based upon the  
19    type of resource that is associated with an operation of a function.

20  
21       **16.**     The method of claim 14, wherein the second criteria is based upon  
22    the nature of an operation of a function on a particular resource.

1        **17.**    The method of claim 16, wherein said nature concerns whether a  
2 function creates a resource.

3  
4        **18.**    The method of claim 16, wherein said nature concerns whether a  
5 function does not create a resource.

6  
7        **19.**    The method of claim 14, wherein the first criteria is based upon the  
8 type of resource that is associated with an operation of a function, and the second  
9 criteria is based upon the nature of an operation of a function on a particular  
10 resource.

11  
12       **20.**    The method of claim 14, wherein at least one interface inherits from  
13 another interface.

14  
15       **21.**    The method of claim 14, wherein at least one interface aggregates.  
16 with another interface.

17  
18       **22.**    The method of claim 14 further comprising instantiating a plurality  
19 of programming objects across a process boundary.

20  
21       **23.**    The method of claim 14 further comprising instantiating a plurality  
22 of programming objects across a process boundary and a machine boundary.  
23  
24  
25

1       **24.**    A method of factoring operating system functions comprising:  
2       factoring a plurality of operating system functions into interface groups  
3       based upon the resources with which a function is associated;  
4       factoring the interface groups into interface sub-groups based upon each  
5       function's use a handle that represents a resource; and  
6       organizing the interface sub-groups so that at least one of the interface sub-  
7       groups inherits from at least one other of the interface sub-groups.  
8

9       **25.**    The method of claim 24, wherein said organizing comprises  
10       aggregating at least one of the interface sub-groups.  
11

12       **26.**    The method of claim 24, wherein the interface sub-groups are  
13       associated with COM objects.  
14

15       **27.**    The method of claim 24, wherein the factoring of the interface  
16       groups into interface sub-groups comprises considering whether a function creates  
17       a handle.  
18  
19  
20  
21  
22  
23  
24  
25

1       **28.**   The method of claim 24, wherein said organizing comprises  
2 aggregating at least one of the interface sub-groups, and wherein the factoring of  
3 the interface groups into interface sub-groups comprises considering whether a  
4 function call creates a handle.

5  
6       **29.**   An operating system application program interface embodied on a  
7 computer-readable medium comprising a plurality of object interfaces, wherein  
8 each object interface includes one or more methods that are associated with and  
9 can call functions of an operating system that does not comprise the object  
10 interfaces.

11  
12       **30.**   The operating system application program interface of claim 29,  
13 wherein the object interfaces are arranged in groups in accordance with the types  
14 of objects with which their operation is associated.

15  
16       **31.**   The operating system application program interface of claim 29,  
17 wherein the methods within some of the interfaces are arranged in accordance with  
18 whether they create an object.

19  
20       **32.**   The operating system application program interface of claim 29,  
21 wherein the methods within some of the interfaces are arranged in accordance with  
22 whether they do not create an object.

33. The operating system application program interface of claim 29, wherein the methods within some of the interfaces are arranged in accordance with whether they operate upon an object.

34. The operating system application program interface of claim 29, wherein at least some of the object interfaces are arranged so that they inherit from other of the object interfaces.

~~35. The operating system application program interface of claim 29, wherein at least some of the object interfaces are arranged so that they aggregate with other of the object interfaces.~~

36. An operating system comprising:  
a plurality of programming objects having interfaces, wherein the programming objects represent operating system resources, and wherein the interfaces define methods that are organized in accordance with whether they create an operating system resource or not;

wherein the programming objects are configured to be called either directly or indirectly by an application; and

wherein the methods are configured to call operating system functions responsive to being called directly or indirectly by an application.

37. The operating system of claim 36, wherein some of the objects are disposed across at least one process boundary.

1        38.    The operating system claim 36, wherein some of the objects are  
2 disposed across at least one machine boundary.

3  
4        39.    The operating system application program interface of claim 36,  
5 wherein at least some of the objects are disposed across at least one process  
6 boundary and at least one machine boundary.

7  
8        40.    The operating system application program interface of claim 36,  
9 wherein the objects comprise COM objects.

10  
11       41.    A method of converting an operating system from a non-object-  
12 oriented format to an object oriented format, wherein the operating system  
13 includes a plurality of operating system functions that are callable to create or use  
14 operating system resources, the method comprising:

15        defining a plurality of programming object interfaces that define methods  
16 that correspond to the operating system functions, wherein programming objects  
17 that support the interfaces are callable either directly or indirectly by an  
18 application;

19        calling a programming object interface; and  
20        responsive to said calling, calling an operating system function with a  
21 method of the programming object that supports said programming object  
22 interface.